

VORTICENT C E RANGE

Centrifugal fans



Suitable for domestic, commercial and industrial applications: kitchens, bathrooms, offices, laboratories, factories, shops, laundromats, models, restaurants, bars, theatres, ballrooms, etc.

- **21 models: 9 single-phase and 12 three-phase.**
 - Steel double-coated protected by polyester paint, resistant to atmospheric agents.
 - Manual reset thermal limit control (models 250 and 315).
 - 1-speed motors with ball bearings.
 - Motor support and air vents designed to minimise turbulence and noise levels.
 - Galvanised steel mounting brackets supplied.
 - Electric supply 230 V / 50 Hz for single-phase models and 400 V / 50 Hz for three-phase models.
 - Protection rating: IP55.
 - Insulation class: I. Ⓢ
 - *Conforms to the requirements of the regulation N°327/2011/UE (Lot 11, 1st Tier) set out by the EUP/ErP Directive, effective as of 01.01.2013.*
 - *Available also in ATEX version (certified for use in areas at risk of explosion due to gases and/or dust particles).*
- For all technical and performance informations see the Vortice's Catalogue (Product Guide 21).*

TECHNICAL DATA

	Models	Code	W	A	POLES	RPM	Max Airflow		Max Pressure		Lp dB(A) a 3 m*	Max °C
							m³/h	l/s	mmH ₂ O	Pa		
Single-phase	C 10/2 M	30302	100	0.45	2	2800	300	83.3	25	245	55.5	50
	C 15/2 M	30902	160	0.7	2	2800	450	125	45	441	59	50
	C 20/2 M E	30321	400	1.76	2	2800	890	247	52.6	516	66	50
	C 25/2 M E	30323	430	1.90	2	2800	1000	277	63	618	66.5	50
	C 30/2 M E	30325	740	3.2	2	2800	1420	394.4	84	824	71	50
	C 30/4 M E	30327	132	0.582	4	1400	700	194	19.8	194	55	50
	C 35/4 M E	30330	370	1.60	4	1400	1520	422.2	34	334	61	50
	C 37/4 M E	30332	675	2.95	4	1400	2150	597.2	45.1	442	70	50
	C 40/4 M E	30334	790	3.47	4	1400	2650	736	49.3	483.1	73	50
Three-phase	C 10/2 T	30351	130	0.3	2	2800	270	75	25	245	55.5	50
	C 15/2 T	30951	160	0.6 - 0.35	2	2800	430	119.4	43	422	59	50
	C 20/2 T E	30322	390	0.785	2	2800	244	880	52.9	519	66	50
	C 25/2 T E	30324	470	1.25	2	2800	1060	294.4	59	579	66.5	50
	C 30/2 T E	30326	720	1.50	2	2800	1350	375	85	834	71	50
	C 30/4 T E	30328	110	0.190	4	1400	655	182	13.2	176	55	50
	C 31/4 T E	30329	280	0.60	4	1400	1100	305.6	31	304	61	50
	C 35/4 T E	30331	350	0.70	4	1400	1550	430.6	34	334	61	50
	C 37/4 T E	30333	700	2.10	4	1400	2300	638.9	47	461	70	50
	C 40/4 T E	30335	800	2.15	4	1400	2900	805.6	49	481	73	50
	C 45/4 T E	30336	1900	4.35	4	1400	4500	1250	74	726	70.5	50
	C 46/4 T E	30337	3900	7.00	4	1400	6800	1888.9	98	961	76.5	50

* Sound pressure level measured at 3 m in free field conditions with long-cased appliance in delivery mode, in accordance with standard EN ISO 3741:2009.

ErP data


Directive 2009/125/EC ErP (Energy related Products)

	Models	Code	Measurement cat.	Efficiency cat.	Year of construction	Variable drive	η	N.	(kW) Pe	m³/h q	Pa p	RPM	Spec. ratio <1.04
Single-phase	C 20/2 M E	30321	B	TOTAL	01-01-13	NO	31.9	42.1	0.245	533	527.6	2939	YES
	C 25/2 M E	30323					32.8	42.5	0.298	697	505	2866	
	C 30/2 M E	30325					41.6	50.0	0.465	876	584	2892	
	C 35/4 M E	30330					32.4	42.2	0.278	1009	321.5	1433	
	C 37/4 M E	30332					35.4	43.5	0.476	1463	415.1	1454	
	C 40/4 M E	30334					36.8	44.8	0.537	1812	392.28	1444	
Three-phase	C 20/2 T E	30322					34.3	44.6	0.231	535	533	2931	
	C 25/2 T E	30324					33.3	42.8	0.309	706	524.5	2949	
	C 30/2 T E	30326					43.2	51.8	0.434	866	779.5	2914	
	C 31/4 T E	30329					31.1	42.1	0.180	680.6	295.2	1460	
	C 35/4 T E	30331					41.1	51.5	0.230	1021	222	1443	
	C 37/4 T E	30333					38.1	46.6	0.464	1490	427.6	1475	
	C 40/4 T E	30335	39.0	47.5	0.451	1503	421.7	1478					
	C 45/4 T E	30336	49.7	56.3	0.913	2399	681.5	1472					
C 46/4 T E	30337	41.6	45.7	2.250	4075	827	1470						

* Best efficiency point.

Orientation

The position of a radial fan delivery outlet is represented by a direction of rotation symbol (LG - that is, towards the left or anti-clockwise, looking from the side opposite the air intake inlet) and the angle (in degrees) of the delivery outlet to the reference axis (a straight line perpendicular to the base plane, passing through the axis of rotation), measured in the direction of rotation.



Designation of delivery outlet position for radial fans.

Adjacent example: LG 135

